NOTES:

A. SWITCHES

S-1 CHANNEL SELECTOR
- (0) — CATHODE RAY OSCILLOSCOPE
- (a) — 0.455 MC PANORAMIC
- (b) — 5.25 MC PANORAMIC
- (c) — 30 MC MANUAL SWEEP

S-2 SYNC. SELECTOR
- (+) — OSCILLATORY INTERNAL SYNC.
- (X) — OSCILLATORY INTERNAL SYNC.
- (I) — SERVO INTERNAL SYNC.
- (X) — SERVO EXTERNAL SYNC.
- (P) — SERVO POWER LINE SYNC.

S-3 SWEEP SPEED
- (0) — SWEEP OFF USE HORIZ. INPUT JACK
- (1) (2) (3) — COARSE SWEEP SPEED
- (4) — FASTER

B POTENTIOMETER CONNECTIONS — FRONT VIEW (1 2 3)

C ALL CAPACITOR VALUES GIVEN IN MICROMICROFARADS UNLESS OTHERWISE STATED.

D ALL RESISTOR VALUES GIVEN IN OHMS UNLESS OTHERWISE INDICATED.

E A ALL RESISTORS ½ WATT UNLESS OTHERWISE INDICATED.

CONFIDENTIAL

TEMPLETONE RADIO COMPANY, MYSTIC, CONN.
TITLE SCHEMATIC
DRAWN C. M.
CHECKED
DATE 3-4-44
SCALE NONE
DWG NO 1372
ISSUE G

Panoramic Adapter AN/APA-10—Schematic Diagram